

Transport Temperature Control System
LMK SLIM



DESCRIPTION: Belt driven unit, for small and medium vehicles and deliveries of fresh perishable foodstuffs (ATP class FNAX)

220V or 400V electric stand-by operating version available (condensing unit 270 mm longer).

COMPONENTS:

- Condensing unit
- Evaporating unit
- Belt driven compressor
- Installation kit
- Digital cab control

REFRIGERANT: HFC R-134A - R-404A
 Chlorine: zero

REFRIGERATION POWER: Cooling capacity calculated with ambient temperature of +30°C:

On the road:	0°C	3300 W
	-10°C	2450 W
	-20°C	1650 W

DIMENSION (mm): Condensing unit:
 860 x 765 x 220h (road only)
 1130 x 765 x 220h (240V)

Evaporating unit:

570 x 1100 x 145h

WARRANTY: Available on demand.
 We guarantee that the unit and all its component are free from defects in materials and workmanship starting from date of installation according to the terms (in months) specified in the warranty

Technical specifications may change without notice.

Manufactured and distributed by:



LAURI s.r.l.
 Via G. Di Capi, 11/A - I-46100 MANTOVA
 Tel. +39 0376 302276
 Fax +39 0376 302246
 E mail: info@lauriweb.it
 URL: www.lauriweb.it